

Digital Folding Pedal Exerciser

For Safety:




- Consult your doctor before starting any exercise program.
- Keep children away from Digital Pedal Exerciser while in use.
- Ensure that the Digital Pedal Exerciser is positioned on a solid flat surface.
- **<u>Do Not</u>** wear loose clothing that could become caught or trapped during exercise.
- Please exercise at your own pace and **Do Not** over-exercise which may cause injury.
- **<u>Do Not</u>** exercise in the standing position.
- Capacity: 150 lbs.

Maintenance:

- Regularly check to see all the nuts, bolts and fittings are securely tightened. Periodically, check all moving parts for signs of wear or damage.
- Clean with a dry cloth. **<u>Do Not</u>** use solvent cleaners.

Usage:



unfold to use:

pull each leg all the way open until the push button pops to lock in place





Authorized CE representative: AJW Technology Consulting GmbH Königsallee 106 40215 Düsseldorf (Germany)



turn over for additional information



Digital Folding Pedal Exerciser

Red Mode/Reset Button:

Function selection and confirm key

Function:

- (A) RPM: Displays rotations per minute.
- **(B)** <u>SCAN:</u> Automatically scans through each function.
- (C) CNT: COUNT UP- Records number of rotations during workout 0 9999.
- (D) TIME: COUNT UP- Displays elapsed exercise time 0:00- 99:59 min.
- **(E)** <u>CAL (CALORIES)</u>: <u>COUNT UP</u>- Displays calorie consumption during exercise.

Note

- Display (LCD panel) shuts off automatically after 4 minutes of non-use. Either press red button or start exercising to restart.
- 2. Requires three (3) AAA batteries.


Installation of counter (F):

- 1. Untighten and remove knob.
- 2. Push the counter into the pedal exerciser and make sure the sensor is on the same side of the magnetic ring.
- 3. Replace knob and tighten.

How to change the battery:

- 1. Untightened knob and take away the knob
- 2. Then pull the counter out from pedal exerciser
- 3. Turn the counter mechanism (H) over to access the battery cover (G).
- 4. Press and slide the battery cover (G) to open for access to the battery.
- 5. Replace the battery and make sure that the positive "+" end is on the top as shown.
- 6. Close battery cover (G). Press red button on front to restart.





turn over for additional information