

SAFETY DATA SHEET

SECTION 1. Product and Company Identification

PRODUCT NAME: Ammonia Inhalants

PRODUCT USE: OTC drug used to treat or prevent fainting

Product Code: 1401

Manufacturer's Name: Dynarex Corporation
Manufacturer's Address: 10 Glenshaw Street

Orangeburg, NY 10962

Emergency or Information 888-DYNAREX or 845-365-8200

Phone No.: At other times, contact the local Poison Control Center

SECTION 2. Hazards Identification



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY"



SECTION 3. Composition/information on Ingredients



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

Not applicable Full text of H-phrases: see section 16			
.2. Mixture			
Name	Product identifier	%	GHS-US classification
Ethyl alcohol	(CAS No) 64-17-5	30 - 40	Flam. Liq. 2, H225 Carc. 1A, H350
Ammonia	(CAS No) 7664-41-7	15 - 20	Flam. Gas 2, H221 Compressed gas, H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314

SECTION 4. First-aid measures

4.1. Description of first aid measu	No.
First-aid measures general	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	Remove to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, give artificial respiration. In case of breathing difficulties administer oxygen, by trained personnel. Seek medical attention immediately.
First-aid measures after skin contact	: Immediately flush skin with plenty of water for at least 15 minutes. Remove/Take off immediately all contaminated clothing. Do not rub the skin and eyes after direct contact with the product. Seek medical attention immediately. Wash contaminated clothing before reuse.
First-aid measures after eye contact	In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately get medical attention.
First-aid measures after ingestion	: If the person is fully conscious, make him/her drink water. Never give an unconscious person anything to drink. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. If swallowed, rinse mouth with water (only if the person is conscious).
4.2. Most important symptoms an	f offects, both acute and delayed
Symptoms/Injuries	Causes severe skin burns and eye damage. This material or its emissions may affect the central nervous system and/or aggravate pre-existing disorders.
Symptoms/injuries after inhalation	May cause cancer by inhalation. Prolonged and repeated inhalation of decomposition products may cause a pulmonary oedema. Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination. Irritating to the respiratory system, may cause throat pain and cough. Difficulty in breathing.
Symptoms/injuries after skin contact	May cause severe burns.
Symptoms/injuries after eye contact	Causes serious eye damage. Can cause blindness.
Symptoms/injuries after ingestion	May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Ingestion may cause nausea, vomiting and diarrhea.
4.3. Indication of any immediate in	edical attention and special treatment needed

No additional information available



Corporate Headquarters

10 Glenshaw Street, Orangeburg, NY 10962 Tel: 845.365.8200 • Fax: 845.365.8201

Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

SECTION 5. Fire-fighting measures

5,1. Extinguishing media	
Suitable extinguishing media	: Alcohol resistant foam. Dry powder. Carbon dioxide. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.
5.2. Special hazards arising from t	he substance or mixture
Fire hazard	: Highly flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.
Reactivity	: Thermal decomposition generates : Corrosive vapours. Reacts violently with acids. An exothermic reaction may occur.
5,3. Advice for firefighters	
Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters	Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Containers may swell and Burst during a fire due to internal pressure caused by heat. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Alcohols burn with a pale blue flame which may be extremely hard to see under normal lighting conditions. Personnel may be able to feel the heat of the fire without seeing flames. Extreme caution must be exercised in fighting alcohol fires.

SECTION 6. Accidental release measures

6.1.	Personal precautions, protective	equipment and emergency procedures
General r	neasures	Eliminate all ignition sources if safe to do so. Use special care to avoid static electric charges. No naked lights. No smoking. Stop leak if safe to do so. No action shall be taken involving any personal risk or without suitable training. Wear protective clothing. For further information refer to section 8: Exposure-controls/personal protection.
6,1,1.	For non-emergency personnel	
Emergen	cy procedures	: Evacuate unnecessary personnel.
6.1.2.	For emergency responders	
Protective	e equipment	: Equip cleanup crew with proper protection.
Emergen	cy procedures	: Ventilate area.
6.2.	Environmental precautions	
Prevent e	entry to sewers and public waters. N	otify authorities if liquid enters sewers or public waters.
6.3,	Methods and material for contain	ment and cleaning up
Methods	for cleaning up	Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Consult the appropriate authorities about wasted disposal. Ensure all national/local regulations are observed.
6.4.	Reference to other sections	
See Head	ding 8. Exposure controls and perso	nal protection.

SECTION 7. Handling and storage



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

7.1. Procautions for safe handling	
Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Personal protective equipment should be selected based upon the conditions under which this product is handled or used. Use personal protective equipment as required. Provide good ventilation in process area to prevent formation of vapour. Do not breathe gas, furnes, vapour or spray. No naked lights. No smoking. Use only non-sparking tools. Never use pressure to empty container. Ground/bond container and receiving equipment. Take care to allow internal pressure to escape from container before releasing closures. Remove closure carefully, internal pressure may be present. Keep closure up to prevent leakage. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Hygiene measures	Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.
7.2 Conditions for sale storage, incl	uding any incompatibilities
Technical measures	: Use explosion-proof machinery, apparatus, ventilation facilities, tools etc. Ensure the ventilation system is regularly maintained and tested. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. A washing facility/water for eye and skin cleaning purposes should be present. Comply with applicable regulations.
Storage conditions	: Keep only in the original container in a cool well ventilated place. Keep in fireproof place, Keep container tightly closed. Protect containers against physical damage. Detached outside storage is preferable. Inside storage should be in an NFPA approved flammable liquids storage room or cabinet. Store in corrosion-proof area at temperatures below 77 degrees F (25oC). Store away from direct sunlight or other heat sources.
Incompatible materials	Avoid mixing with acids, most common metals, strong oxidizing agents, brass, zinc, chlorine, aluminum, copper, bronze, mercury, dimethyl sulfate and acetyl chloride.
7.3. Specific emil usu(a)	
No additional information available	

SECTION 8. Exposure controls/personal protection



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

Appropriate engineering controls

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of mists and/or vapors below the recommended exposure limits. Use explosion-proof ventilating equipment.

Personal protective equipment

Avoid all unnecessary exposure. A hazard assessment of the work area for PPE requirements should be conducted by a qualified professional pursuant to OSHA regulations. For certain operations, additional Personal Protection Equipment (PPE) may be required. Protective goggles. Gloves. Protective clothing.







Hand protection

Wear protective gloves, rubber gloves. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of

Eye protection

- Chemical goggles or face shield.
- Skin and body protection
- Wear suitable protective clothing. Chemical resistant safety shoes.

Respiratory protection

Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals. Care must be taken to assure that any respirator chosen is capable of protecting the user from both ammonia and ethyl alcohol vapors.

Other information

: Do not eat, drink or smoke during use.

SECTION 9. Physical and chemical properties



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

9.1. Information on basic physical an	d chemical properties	
Physical state	: Liquid	
Appearance	: Clear.	
Colour	: Red.	
Odour	: Pungent ammonia odour.	
Odour threshold	: No data available	
pH	: No data available	
Relative evaporation rate (butyl acetate=1)	: No data available	
Melting point	: No data available	
Freezing point	: No data available	
Boiling point	: > 35 °C (> 95 °F)	
Flash point	: < 10 °C (< 50 °F - Pensky Martens Closed Cup)	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapour pressure	: No data available	
Relative vapour density at 20 °C	: No data available	
Relative density	: No data available	
Density	: 0.891 (Specific Gravity @ 25 °C)	
Solubility	: Soluble in water.	
Log Pow	: No data available	
Log Kow	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
Explosive properties	: No data available	
Oxidising properties	: No data available	
Explosive limits	: No data available	
9.2. Other information		
No additional information available		

SECTION 10. Stability and reactivity



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

10.1. Reactivity

Thermal decomposition generates: Corrosive vapours. Reacts violently with acids. An exothermic reaction may occur.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Avoid mixing with acids, most common metals, strong oxidizing agents, brass, zinc, chlorine, aluminum, copper, bronze, mercury, dimethyl sulfate and acetyl chloride.

10.6. Hazardous decomposition products

Thermal decomposition generates: Fume. Carbon monoxide. Carbon dioxide. May release flammable gases. Corrosive vapours. Ammonia. Nitrogen oxides. release of highly flammable gases/vapours hydrogen.

SECTION 11. Toxicological information



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

Acute toxicity	: Not classified
	(Based on available data, the classification criteria are not met)
Ammonia (7664-41-7)	
LD50 oral rat	350 mg/kg
LC50 inhalation rat (ppm)	2000 ppm/4h
Ethyl alcohol (64-17-5)	
LC50 inhalation rat (mg/l)	124.7 mg/l (Exposure time: 4 h)
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified
	(Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified
	(Based on available data, the classification criteria are not met)
Carcinogenicity	: May cause cancer.
Ethyl alcohol (64-17-5)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	: Not classified
	(Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: Not classified
	(Based on available data, the classification criteria are not met)
Specific target organ toxicity (repeated	: Not classified
exposure)	(Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified
	(Based on available data, the classification criteria are not met)
Potential Adverse human health effects and symptoms	Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	May cause cancer by inhalation. Prolonged and repeated inhalation of decomposition products may cause a pulmonary oedema. Depression of the central nervous system, headaches dizziness, drowsiness, loss of coordination. Irritating to the respiratory system, may cause throat pain and cough. Difficulty in breathing.
Symptoms/injuries after skin contact	: May cause severe burns.
Symptoms/injuries after eye contact	: Causes serious eye damage. Can cause blindness.
Symptoms/injuries after ingestion	: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Ingestion may cause nausea, vomiting and diarrhea.

SECTION 12. Ecological information



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

Ammonia (7664-41-7)	
LC50 fishes 1	0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio)
EC50 Daphnia 1	25.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	0.26 - 4.6 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
Ethyl alcohol (64-17-5)	
LC50 fishes 1	12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 2	10800 mg/l (Exposure time: 24 h - Species: Daphnia magna)
2.2. Persistence and degradability	
Ammonia Inhalant Solution	
Persistence and degradability	Not established.
2.3. Bioaccumulative potential	
Ammonia Inhalant Solution	
Bioaccumulative potential	Not established.
Ammonia (7664-41-7)	
Log Pow	-1.14 (at 25 °C)
Ethyl alcohol (64-17-5)	
Log Pow	-0.32
12.4. Mobility in soil	
No additional information available	
2.5. Other adverse effects	
Other information	: Avoid release to the environment.

SECTION 13. Disposal considerations

13.1. Waste treatment methods	
Waste disposal recommendations	Dispose in a safe manner in accordance with local/national regulations. Do not re-use empty containers. Ensure all national/local regulations are observed. Consult the appropriate authorities about waste disposal.
Additional information	: Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14. Transport information



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY"

In accordance with DOT

Transport document description

UN-No.(DOT) DOT NA no

DOT Proper Shipping Name

Department of Transportation (DOT) Hazard

Hazard labels (DOT)

: UN2924 Flammable liquids, corrosive, n.o.s. (Ammonia, Ethanol), 3, II

: UN2924

: Flammable liquids, corrosive, n.o.s.

(Ammonia, Ethanol)

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173,120

3 - Flammable liquid

8 - Corrosive





DOT Symbols

: G - Identifies PSN requiring a technical name

Packing group (DOT)

DOT Special Provisions (49 CFR 172.102)

: II - Medium Danger

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, if is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59

F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as

defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Packaging Non Bulk (49 CFR 173.xxx)

DOT Packaging Bulk (49 CFR 173.xxx)

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173,27)

DOT Quantity Limitations Cargo aircraft only (49 : 5 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other 40 - Stow "clear of living quarters"

: 150

: 11

202

243

Additional information

Other information

: No supplementary information available.

ADR

Transport by sea

: No additional information available

No additional information available

Transport document description

Air transport

No additional information available



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

SECTION 15. Regulatory information

Ammonia Inhalant Solution	
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	588 lb
Ammonia (7664-41-7)	
Listed on the United States TSCA (Toxic Substat Listed on SARA Section 302 (Specific toxic chem Listed on SARA Section 313 (Specific toxic chem	nical listings)
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	1.0 % (includes anhydrous Ammonia and aqueous Ammonia from water dissociable Ammonium salts and other sources, 10% of total aqueous Ammonia is reportable under this listing)
Ethyl alcohol (64-17-5)	
Listed on the United States TSCA (Toxic Substan	nces Control Act) inventory
5.2. International regulations	
5.2. International regulations ANADA Ammonia (7664-41-7)	
5.2. International regulations ANADA Ammonia (7664-41-7) Listed on the Canadian DSL (Domestic Sustance	
5.2. International regulations ANADA Ammonia (7664-41-7) Listed on the Canadian DSL (Domestic Sustance WHMIS Classification	es List) inventory. Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material
5.2. International regulations ANADA Ammonia (7664-41-7) Listed on the Canadian DSL (Domestic Sustance WHMIS Classification Ethyl alcohol (64-17-5) Listed on the Canadian DSL (Domestic Sustance	es List) inventory. Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material
5.2. International regulations ANADA	es List) inventory. Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material
5.2. International regulations ANADA Ammonia (7664-41-7) Listed on the Canadian DSL (Domestic Sustance WHMIS Classification Ethyl alcohol (64-17-5) Listed on the Canadian DSL (Domestic Sustance WHMIS Classification	es List) inventory. Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material ss List) inventory. Class B Division 2 - Flammable Liquid
5.2. International regulations ANADA Ammonia (7664-41-7) Listed on the Canadian DSL (Domestic Sustance WHMIS Classification Ethyl alcohol (64-17-5) Listed on the Canadian DSL (Domestic Sustance WHMIS Classification U-Regulations	es List) inventory. Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material ss List) inventory. Class B Division 2 - Flammable Liquid
5.2. International regulations ANADA Ammonia (7664-41-7) Listed on the Canadian DSL (Domestic Sustance WHMIS Classification Ethyl alcohol (64-17-5) Listed on the Canadian DSL (Domestic Sustance WHMIS Classification U-Regulations Ammonia (7664-41-7)	es List) inventory. Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material ss List) inventory. Class B Division 2 - Flammable Liquid



Toll-Free: 888.DYNAREX

WE CARE LIKE FAMILY™

Classification according to Regulation (EC) No. 1272/2008 [CLP] Not classified Classification according to Directive 67/548/EEC or 1999/45/EC Not classified 15.2.2. National regulations Ammonia (7664-41-7) Listed on the AICS (the Australian Inventory of Chemical Substances) Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory. Listed on the Korean ECL (Existing Chemical List) inventory. Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS) Poisonous and Deleterious Substances Control Law Listed on the Canadian Ingredient Disclosure List Ethyl alcohol (64-17-5) Listed on IARC (International Agency for Research on Cancer) Listed on the AICS (the Australian Inventory of Chemical Substances) Listed on Inventory of Existing Chemical Substances (IECSC) Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory. Listed on the Korean ECL (Existing Chemical List) inventory. Listed on New Zealand - Inventory of Chemicals (NZIoC) Listed on Inventory of Chemicals and Chemical Substances (PICCS) Listed on the Canadian Ingredient Disclosure List 15.3. US State regulations Ethyl alcohol (64-17-5) No significance risk level (NSRL) U.S. - California Proposition 65 -U.S. - California -U.S. - California -U.S. - California -Proposition 65 -Proposition 65 -Proposition 65 -Reproductive Toxicity -Carcinogens List **Developmental Toxicity** Reproductive Toxicity - Male Female Yes Yes

SECTION 16. Other information

Disclaimer:

This Safety Data Sheet, which takes into consideration the requirements of Directive 76/768/EC and subsequent amendments and Directive 1999/45/EC plus subsequent amendments, has been prepared in accordance with Directive (EC) 1907/2006. It is believed to be correct and corresponds to the latest scientific/technical knowledge but all data, instructions, recommendations and/or suggestions are made without guarantee. No warranty, expressed or implied, is made and Dynarex Corp. assumes no legal responsibility or liability resulting from its use.