

Open Base Space Saver Power Table with Drop Section

MODEL 80330

- Pneumatic backrest is adjustable from either side and raises 80 degrees from flat
- Drop Section is adjustable from either side and lowers up to 80 degrees from flat
- Standard drop section has nose hole, but it may be ordered without a nose hole (Please specify when ordering)
- Electric power height adjustment with foot control
- Ultra-strong, uni-frame base and top construction
- Heavy duty, all welded, lift mechanism
- Durable gray powder-coated steel frame
- Self-lubricating pivot points
- Smooth 110 volt electric height adjustment
- Power supply and motor meets UL 60601-1 and CAN/CSA C22.2 601.1
- Hands-free low voltage foot control
- Easy service, self contained, electrical components
- Seamless, rounded corner, upholstered top
- 2" ultra-firm padding
- Low height may help achieve ADA tax credit
- Customize with options
- Made in the USA by Clinton Industries
- 500 lbs. (227 kg) load capacity under normal use

California residents please be advised of the following, pursuant to Proposition 65:

MARNING: This product can expose you to chemicals, including chromium, which is known to the State of California to cause cancer or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

POWER 500



80330 SPECIFICATIONS		
Overall	76" L x	27" W x 18–35" H
Backrest	38" L x	27" W
Footrest	13" L x	27" W





OPTIONS

Positioning Straps Set

- 2"x 92" strap is secured with quick hook and loop Velcro® fasteners
- 2 straps per set (92" x 2")

080

Safety Rails (pair)

- 3 height positions
- Plunger height adjustment

082

Hand-Held Controller

- Alternative to foot control
- Stores easily under top when not in use

084

Locking Casters

• Heavy duty, rubber wheel, easy-roll casters

087

030 Paper Dispenser

• Accommodates paper rolls from 18" (45.72cm) to 21" (53.34cm) wide

030

Paper Cutter

• Clear plastic with elastic strap and buckle

040

Paper Dispenser/Cutter Combo

• Paper dispenser and paper cutter ordered as one option

034



030

